



### FEATURES 設備特性

1. Equipped with spray nozzle and spray tip for swirl coating. Various size of spray tip is available.  
搭配不同尺寸的噴片，來做不同大小的出膠塗佈。
2. Buckle cup tank and easy open handle for easy operation and good safety.  
膠槽開關採用安全扣環設計，易開罐式手把，操作簡單，安全不氣爆。
3. Spray applies to shoe upper, interlining, shoe tongue.  
採用噴霧方式時可噴鞋面，鞋內裡，鞋舌等部位。
4. Small volume for easily moving, dispensing for bead, line or spray shape is available.  
體積小，移動方便，功能齊全，可選擇條狀、點狀、霧狀噴嘴。

### SPECIFICATIONS 設備規格

SPEC 規格	UNIT 單位	HS0753S-2T
Tank Capacity 膠槽容量	Liter	1
Max. Melting Rate 最大熔膠速率	Kg/HR	2.5
Max. Operation Temp. 最高操作溫度	°C	220
Max. Viscosity 最大使用黏稠度	CPS	12000
Available Gun 噴槍數目	Set	1
Tank Air Pressure 膠桶氣壓範圍	Kg/cm <sup>2</sup>	4
Dimensions (L x W x H) 尺寸 (長 x 寬 x 高)	mm	360 x 510 x 610
Weight 重量	Kg	Approx. 16
Machine Power Rate 主機總功率	Watt	1340
Machine Power Requirement 主機電力需求		220V AC, 6.1A, 60Hz, 1Φ

