

FEATURES 設備特性

1. Melting tank, dispensing nozzle and hose could be heated orderly to avoid the nozzle over heat and to reduce the carbonization.
熔膠槽與保溫管、噴槍順序加熱，避免保溫管、噴槍加熱時間過長，減少膠質碳化、節省用電。
2. Weekly timer for setting the time to turn on and off the machine automatically by requirements.
全週預約開關機功能，可依實際功能需求設定每天不同的開關機時間。
3. The function of keep warm as a "Stand-By" status to reduce the carbonized of the hot melt and meet the envelopment friendly purpose.
停機保溫功能，減少膠質碳化符合環保節能需求。
4. The function of warning malfunction.
故障警報警示功能。
5. The gear pump is install vertically for stable the glue pumping rate and easy for maintenance.
齒輪泵浦獨立懸吊系統，出膠穩定，保養、維修省時方便。
6. With a precision glue flow adjustor valve and electrical inverter for the motor to ensure the glue flow satiability.
精密流量調節開關，搭配電子式變頻器，可使出膠量調整精確。
7. Double layer stainless steel filter net to catch the impurities for extend the machine life.
雙層不鏽鋼過濾網，有效過濾雜質，延長機器使用壽命。
8. Individual temperature control with digital controller for melting tank, dispensing nozzle and hose.
全數位顯示功能，熔膠槽、噴頭與保溫管獨立控溫顯示。



SPECIFICATIONS 設備規格

SPEC 規格	UNIT 單位	HS110C2	HS110C4
Tank Capacity 膠槽容量	Liter	10	10
Max. Melting Rate 最大熔膠速率	Kg/HR	10	10
Max. Operation Temp. 最高操作溫度	°C	200	200
Max. Viscosity 最高使用黏度	CPS	30000	30000
Available Hose/Gun 保溫管/噴槍數目	Set	1 - 2	1 - 4
Glue Flow per Pump 單泵出膠速率	g/MIN	400	400
Dimensions (L x W x H) 尺寸(長 x 寬 x 高)	mm	700 x 430 x 470	700 x 430 x 470
Weight 重量	Kg	Approx. 65	Approx. 65
Melting Tank Power 熔膠槽加熱功率	Watt	3000	3000
Power Requirement 電力需求		220V AC, 22A, 50/60Hz, 1Φ	220V AC, 28A, 50/60Hz, 1Φ

The flow rate depends on the viscosity of hot melt adhesive.
實際出膠量會依熱熔膠的黏稠度改變

HWANG SUN ENTERPRISE CO., LTD. 皇尚企業股份有限公司

ISO 9001:2008 SGS REGISTERED FIRM

Headquarters 臺灣總公司

No. 8, Keji 1st Rd.,
Annan District, Tainan 70955, Taiwan
70955 台南市安南區科技一路8號(科工區)
TEL: +886-6-3842889 FAX: +886-6-3842868

Machinery Divison 機械事業中心

No.15, Hsin Ho 2nd Rd.,
Ann-Ping Industrial District, Tainan 70248, Taiwan
70248 台南市安平工業區新和二路15號
TEL: +886-6-2644191 FAX: +886-6-3842868

Taichung 台中營業所

4F-4, No. 82, Daying W. 1st St.,
Nantun District, Taichung 40865, Taiwan
40865 台中市南屯區大英西一街 82 號 4 樓之 4
TEL: +886-4-24739593 FAX: +886-4-24714414

Taipei 台北營業所

1F, No. 25-1, Hami St.,
Datong District, Taipei 10370, Taiwan
10370 台北市哈密街 25 之 1 號 1 樓
TEL: +886-2-25933744 FAX: +886-2-25923570

Suzhou 蘇州辦事處

Building No. 28, Li Tang Road, Kua Tang Town, Su Zhou
Industrial Park, Su Zhou City, Jiang Su Province, China
江蘇省蘇州市園區跨塘鎮蠡塘路逸苑別墅 28 棟
TEL: +86-512-67865516 FAX: +86-512-68557601

Dongguan Hwang Sun Industrial Co., Ltd. 東莞皇尚實業有限公司

Behind the Dongying Restaurant (Catty corner from No.
36 Liaoxia Rd., Liaoxia Ave.), Provincial Highway S256,
Liaoxia Village, Houjie Town, Dongguan 523960, China
中國東莞市厚街鎮寮廈村 S256 省道旁東盈酒店後
(寮廈大道寮廈路 36 號斜對面)
TEL: +86-769-81636099 FAX: +86-769-81636399