

HS7006D PUR 滾輪上膠機 HS7006D PUR Roller Applicator



鞋面過膠

腳床過膠

EVA過膠

Coating shoe bed,
EVA midsole, upper in sandal making

產品規格(SPECIFICATION):

項目 Item	UNIT	7006D
膠槽容量 Tank capacity	LITER	0.3
最大黏稠度 Max.cps	CPS	200,000
最大操作溫度 Max.operation temp	℃	220
過膠寬度 Roller width	MM	180
最大耗電量 Max.power rate	WATT	2,540
電力需求 Power requirement		220VAC/50HZ
尺寸 Dimension:L×W×H	MM	600×610×1650
重量 Weight	KG	130

產品特性:

1. 本機是HS2506熔膠機配套機種。
2. 採用PID控溫及變頻器調速，更精密與穩定。
3. 維護容易，可在6分鐘內更換滾輪，進行清洗。
4. 三槽設計(膠槽、清洗劑槽、清洗承接槽)，補膠與清洗膠槽配合默契。
5. 三色警示燈指示操作狀態，更有效，操作更方便。
6. 密閉式融膠槽，可充填表氮氣防止膠質碳化或化學反應。
7. 適用於濕氣反應型熱熔膠，融膠槽配備精密液開關，可搭配自動補膠系統(HS2506)採用上方塗膠設計,操作方便不粘手。
8. 過膠厚度、速度可調。
9. 防卷手設計，確保作業安全。

FEATURE :

1. This machine works together with PUR drum melter HS2506G-E.
2. Temperature controlled by PID, and roller rate controlled by VFD, for higher precision and more stability.
3. Easy to maintenance.
A dirty roller can be unloaded and cleaned and reloaded within 6 minutes.
4. 3-tank design (roller heating tank, cleaner tank ,cleaner tray).
Easy to switch between cleaning and PUR supplying.
5. 3-color indicator to show operation status, which brings more efficiency and convenience.
6. Coating substrate from upper roller, pressing it from lower roller.
7. Anti-drawn-in device for good safety.

