

產品規格(SPECIFICATION):

項目 Item	UNIT	7006H
膠槽容量 Tank capacity	LITER	0.4
膠桶容量 Barrels capacity	LITER	8
最大熔膠速率 Max.melting rate	KG/HR	15
最大黏稠度 Max.cps	CPS	200,000
最大操作溫度 Max.operation temp	℃	220
滾輪寬度 Roller wirth	MM	180
最大耗電量 Max.power rate	WATT	5,700
電力需求 Power requirement		220VAC/60HZ
尺寸 Dimension:L×W×H	MM	670×740×1750
重量 Weight	KG	180

產品特性:

1. 兼備熔膠和過膠功能。
2. 採用PLC控制，安全設計，不易碳化。
3. 自動檢測膠量剩餘裝置，可進行自動及手動補膠。
4. 出膠量均勻且穩定，上膠厚度可調在1.2~1.5mm之間。
5. 有壓花滾輪、光面滾輪供選擇，還可依工作需求特制滾輪。
6. 防卷手設計。

FEATURE :

1. This machine works as a melter and coater.
2. PLC built-in control panel ensures good safety and less charring.
3. Automatically check HMMC remains.
Automatical operation for coating, and manual operation for clearing tank/hose/roller.
4. Even and smooth flow rate.
Coating thickness ranges within 1.2mm and 1.5mm.
5. Embossing roller, flat roller and other specially made roller are optional.



轉印膠 → 貼合于橡膠外底

Coating substrates → Attaching
Transferring to Rubber Outsole
Detaching from Substrate



中底過膠 → 中底和外底橡膠貼合
Coating injection polyesters midsole → Attaching