



### FEATURES 設備特性

1. Without pressing roller, immediately paste and stick on required material. Coating thickness is adjustable. Suitable for material that needed to be coated whole surface, like flat wood and foam, etc.  
單一過膠滾輪，即抹即貼，上膠厚度可調整，適合平面上膠的物料，如木板、泡棉等。
2. Equipped with inverter to precisely control speed of roller.  
配有變頻器可精準調節滾輪速度。
3. Individual temperature control system for melting tank and roller.  
膠槽與滾輪分別為獨立加熱系統。
4. Equipped with isolation tank cover, emergency stop switch and cantilever for operational safety.  
採用膠槽護罩，滾輪防護罩以及緊急停止開關，以防捲手。

### SPECIFICATIONS 設備規格

SPEC 規格	UNIT 單位	HS7008-B
Tank Capacity 膠槽容量	Liter	5
Max. Melting Rate 最大熔膠速率	Kg/HR	7
Max. Operation Temp. 最高操作溫度	°C	220
Max. Viscosity 最大黏稠度	CPS	20000
Roller Width 上膠寬度	mm	600
Dimensions (L x W x H) 尺寸(長 x 寬 x 高)	mm	850 x 380 x 400
Weight 重量	Kg	Approx. 94
Machine Power Consumption 主機功率	Watt	3600
Power Requirement 電力需求		220V AC / 50/60Hz / 1Φ

**Tainan Headquarters 台南總公司**

No. 8, Keji 1st Rd.,  
Annan District, Tainan 70955, Taiwan  
70955 台南市安南區科技一路 8 號 (科工區)  
TEL: +886-6-3842889 FAX: +886-6-3842868

**Taichung 台中**

4F-4, No. 82, Daying W. 1st St.,  
Nantun District, Taichung 40865, Taiwan  
40865 台中市南屯區大英西一街 82 號 4 樓之 4  
TEL: +886-4-24739593 FAX: +886-4-24714414

**Taipei 台北**

1F, No. 25-1, Hami St.,  
Datong District, Taipei 10370, Taiwan  
10370 台北市哈密街 25 之 1 號 1 樓  
TEL: +886-2-25933744 FAX: +886-2-25923570

**Suzhou 蘇州**

Building No. 28, Li Tang Road, Kua Tang Town, Su Zhou  
Industrial Park, Su Zhou City, Jiang Su Province, China  
江蘇省蘇州市園區跨塘鎮蠡塘路逸苑別墅 28 棟  
TEL: +86-512-67865516 FAX: +86-512-68557601

**Dongguan HUANGSHANG Industries Co., Ltd.  
東莞皇尚實業有限公司**

Behind the Dongying Restaurant (Catty corner from No.  
36 Liaoxia Rd., Liaoxia Ave.), Provincial Highway S256,  
Liaoxia Village, Houjie Town, Dongguan 523960, China  
東莞市厚街鎮寮廈村 S256 省道旁東盈酒店後  
(寮廈大道寮廈路 36 號斜對面)  
TEL: +86-769-81636099 FAX: +86-769-81636399